### WHO WE ARE

Astotec Automotive specializes in the development and production of advanced pyrotechnic solutions for systems that protect pedestrians and occupants, as well as for non-automotive applications.

Our highly innovative developments deliver technological and competitive advantages wherever they are applied.

### **OUR CUSTOMERS**

With our outstanding research and development track record and our long manufacturing experience, Astotec Automotive is the ideal partner at every stage of the development process, from initial concepts to pre-production to volume manufacturing. Our extensive manufacturing resources provide great cost efficiencies while assuring that our products meet very rigorous quality demands.

### **FULL CAPABILITIES IN HOUSE**

Advanced equipment to evaluate all product parameters. Immediate analysis and actionable results within the hour. Changes can be made at very short notice. Fast decision-making for product optimization. Current source for testing of electric components is a capacitor bank generating 30.000 A at 1000V DC. Complete in-house environmental testing available.



### **Astotec Automotive GmbH**

Leobersdorfer Strasse 31-33 2552 Hirtenberg / Austria Phone: +43 2256 811 84 E-Mail: automotive.at@astotec.com

### Astotec Automotive North America, Inc

3201 University Drive / Suite 150 Auburn Hills / MI 48326 / USA E-Mail: automotive.us@astotec.com

#### automotive.astotec.com









# **PUSHING ACTUATORS**

FOR ACTIVE HINGES & LATCHES

The actuator can fulfill following functions, based on your requirements and specifications:

- Fixation starting position
- Fixation end positionNVH conformity
- Defined retention force over time
- Resetting after reaching end position
- Resetting with defined force
- Damping head impact
- Oscillation damping



CHARACTERISTICS	
Actuator type	Pushing piston
Activation time	2 - 40 ms
Piston stroke	5 - 130 mm
F max	7 500 N
Fixation forces start position end position	1 000 N 5 000 N
Design	Linear
Interfaces	Leadwire or Pintype
Noise exposure	< 95 dB
BAM approval	CE-Conformity acc. EU-Pyrotechnical Directive 2007 / 23 / EG
Specification	According customers demand

#### BENEFITS

- Extreme fast reaction timesStable and reliable performance over lifetime
- Compact and robust design
- No flaming and no hot gases
- Various integration options possible Cost efficient & light weight

# PEDESTRIAN PROTECTION

ADVANCED PYROTECHNIC SOLUTIONS

Active hood systems provide clearance between hood and engine in the event of a pedestrian collision by lifting the hood. The generated clearance grants that the head does not hit rigid components.

The actuators rise the hood directly or can be integrated within the hinges or latches. Our customers benefit from our experience as market leader for pyrotechnic actuators. This leads to reduced development time, efforts and costs.



# **Astotec Automotive DEVELOPMENT CENTER**





- Prototyping fast & precise, time & cost savingExtreme fast modifications possible
- Testing in system environmentImmediate analysis after testing
- Development & support from concept to series